

aSK10

10" Passive 2-way Stage Speaker / Floor
Monitor 200 Watt Power Handling (Music)

aSK12

12" Passive 2-way Stage Speaker / Floor
Monitor 400 Watt Power Handling (Music)

aSK15

15" Passive 2-way Stage Speaker / Floor
Monitor 400 Watt Power Handling (Music)

aSK215

Dual 15" Passive 2-way Stage Speaker
800 Watt Power Handling (Music)

aSK18

18" Subwoofer
600 Watt Power Handling (Music)

aSK10 | aSK12 | aSK15 | aSK215 | aSK18



Features

- ▶ RMS power ratings certified and tested using the IEC 268 torture test
- ▶ New 1.3" pure titanium compression tweeter paired with Phonic's proprietary Wing-Guide™ horn delivers smooth, transient highs beyond 20kHz
- ▶ Wide 90°x70° dispersion angle
- ▶ Long-throw Black Morie woofers give added bass "thump"
- ▶ Stability bracing system increases structural strength
- ▶ Input and Output: Parallel ¼" jacks
- ▶ Serves as floor monitor when tilted on the side (aSK10/12/15)
- ▶ Thick 1.3" grille to withstand the bumps and bruises of the road
- ▶ Metal handles and pole mounts are exceptionally ergonomic and virtually indestructible

Description

In developing the aSK, Phonic's Loudspeaker Research and Development Team insisted on professional grade performance at affordable price points to fit the needs of performers and hobbyists alike. Engineered from the ground up, the aSK is built like a tank. Structural features include internal bracing that minimize body vibration, heavy duty metal handles, slanted sides to decrease diffraction, and ultrathick (Yes! Ultra-thick!) carpet to withstand the occasional, unavoidable, rough handling. The aSK is also equipped with Phonic's proprietary Wing-Guide™ horn which lowers distortion and improves dispersion consistency. Phonic's Loudspeaker R&D Team also engineered new drivers for the series including 1.3" pure titanium tweeters and long-throw woofers, resulting in a stellar acoustic response that is flat overall with a bass boost providing added "thump". For rigorous performance requirements at an incredible value - the aSK makes no compromises.

aSK SPEAKER SERIES

Professional Passive Speakers

Dimensions

aSK10 | aSK12 | aSK15 | aSK215 | aSK18

Back Panel



Specifications

	aSK10	aSK 12	aSK 15	aSK 215	aSK 18
System Specifications					
System Type	2-way	2-way	2-way	2-way	Subwoofer
Frequency Response (+/- 3dB)	65Hz-20kHz	50Hz-20kHz	45Hz-20kHz	40Hz-20kHz	40Hz-250Hz
RMS(IEC 268) / Music / Peak	100/200/400w	200/400/800w	350/700/1400W	700/1400/2800W	500/1000/2000W
Sensitivity 1w@1m	96dB	97dB	98dB	99dB	99dB
System Impedance	8ohm	8ohm	8ohm	4ohm	4ohm
Low Frequency Driver					
Driver Size	255mm/10in	305mm/12in	380mm/15in	380mm/15in	470mm/18in
Diaphragm Material	Black Morie Paper	Black Morie Paper	Black Morie Paper	Black Morie Paper	Black Morie Paper
Voice Coil Diameter	36.5mm/1.5in	51mm/2.0in	66mm/2.6in	66mm/2.6in	100mm/4.0in
High Frequency Driver					
Voice Coil Diameter	32mm/1.3in	32mm/1.3in	45mm/1.8in	45mm/1.8in	-
Diaphragm Material	Pure Titanium	Pure Titanium	Pure Titanium	Pure Titanium	-
Horn Design	Wing-Guide"	Wing-Guide"	Wing-Guide"	Wing-Guide""	-
System Dispursion	90°x70°	90°x70°	90°x70°	90°x70°	-
Crossover					
Type	2-way full range	2-way full range	2-way full range	2-way full range	Subwoofer
Protection	PTC Protection	PTC Protection	PTC Protection	PTC Protection	-
Input/Outputs					
Connectors	1/4" Parallel Inputs	1/4" Parallel Inputs	1/4" Parallel Inputs	1/4" Parallel Inputs	Speakon x 2
Enclosure					
Shape/Type	Stage Speaker and Stage Monitor	Stage Speaker and Stage Monitor	Stage Speaker and Stage Monitor	Stage Speaker	Stage Speaker
Box Protection/Finish	Ultra-Thick Carpet	Ultra-Thick Carpet	Ultra-Thick Carpet	Ultra-Thick Carpet	Ultra-Thick Carpet
Wood Thickness	15mm/0.6in	15mm/0.6in	15mm/0.6in	20mm/0.8in	20mm/0.8in
Grille Gauge	1.3mm	1.3mm	1.3mm	1.3mm	1.3mm
Wood Type	MDF Front/ Chipboard Sides	MDF Front/ Chipboard Sides	MDF Front/ Chipboard Sides	Grade-A MDF	Grade-A MDF
Bracing	Stabilty Bracing System	Stabilty Bracing System	Stabilty Bracing System	Stabilty Bracing System	Stabilty Bracing System
Sound Ports	50mm x 2pcs	50mm x 2pcs	60mm x 2pcs	60mm x 2pcs	146(Diameter)x 159(Length) x2pcs
Pole Mount	Metal Pole Mount	Metal Pole Mount	Metal Pole Mount	Metal Pole Mount	Metal Pole Mount
Handles	Egronomic Metal Handle	Egronomic Metal Handles	Egronomic Metal Handles	Egronomic Metal Handles	Egronomic Metal Handles
Unit Dimensions (HxWxD)	578x385x307mm /22.8x15.6x12.1in	607x405x323mm /23.9x15.9x12.7in	705x470x375mm /27.8x18.5x14.8in	1100x470x470mm / 43.3x18.5x18.5in	535x620x620mm /21.1x24.4x24.4in
Weight	15kg/33lbs	16.5kg/36.3lbs	21kg/46.2lbs	44.5kg/97.9lbs	44kg/96.8lbs

Information in this document is subject to change without notice.

Page 2