

iSK8 Deluxe

350W 8" Passive 2-way Stage Speaker / Floor Monitor

iSK10 Deluxe

400W 10" Passive 2-way Stage Speaker / Floor Monitor

iSK12 | iSK12 Deluxe

700W 12" Passive 2-way Stage Speaker / Floor Monitor

iSK15 | iSK15 Deluxe

700W 15" Passive 2-way Stage Speaker / Floor Monitor

iSK215 | iSK215 Deluxe

1400W Dual 15" Passive 2-way Stage Speaker

iSK18SB | iSK18SB Deluxe

1000W 18" Passive Subwoofer



Features

- ▶ RMS power ratings certified and tested using the IEC 268 torture test
- ▶ 1" or 1.8" pure titanium compression tweeter paired with Phonic's proprietary horn delivers smooth, transient highs beyond 22kHz
- ▶ Internal bracing system increases structural strength
- ▶ New long-throw composite woofers
- ▶ Wide 90° x 70° dispersion angle (model dependent)
- ▶ Professional Speakon In/Out Connections for more secure setups
- ▶ Serves as a floor monitor when tilted on the side (iSK8/10/12/15)
- ▶ Powder coated 18 gauge steel with acoustically transparent foam
- ▶ Ergonomic metal handles on the iSK and integrated handles on Deluxe models
- ▶ Thick carpet protection on regular models, tough 3-layer scratch-proof paint on Deluxe models

Description

With its signature vertical curvatures, thick foamed grille, and ergonomic metal handles, the studio-tuned iSK establishes itself as the new segment benchmark. The iSK's new 1.8" pure titanium compression tweeters gracefully extends beyond 22kHz and long-throw woofers reaches lower FO's than other woofers on the market. The iSK series is the most versatile in its class with 35mm standard pole mounts, 45° floor monitor position for two-way models and M10 suspension points on the Deluxe models. Finally, the iSKs are incredibly heavy-duty with either tough anti-scratch paint (Deluxe) or professional-grade carpeting (Original). iSK models are constructed from 15 to 18 mm thick Grade-A MDF panels, engineered for unsurpassed audio response, sensational power handling, and extensive mounting possibilities, the iSK establishes a new benchmark.

ISK SERIES

Professional Passive Loudspeakers

Back Panel



Specifications

Model Name	iSK 8 Deluxe	iSK 10 Deluxe	iSK 12 (Deluxe)	iSK 15 (Deluxe)	iSK 215 (Deluxe)	iSK 18SB (Deluxe)
System Type	8" 2-Way Stage Speaker & Floor Monitor	10" 2-Way Stage Speaker & Floor Monitor	12" 2-Way Stage Speaker & Floor Monitor	15" 2-Way Stage Speaker & Floor Monitor	Dual 15" 2-Way Stage Speaker	18" Subwoofer
Frequency Response (+/- 3dB)	70Hz - 20kHz	65Hz - 20kHz	52Hz - 22kHz	48Hz - 22kHz	38Hz - 22kHz	35Hz - 250Hz
Power Handling (RMS IEC 268-5)	175W	200W	350W	350W	700W	500W
Power Handling (Music)	350W	400W	700W	700W	1400W	1000W
Power Handling (Peak)	700W	800W	1400W	1400W	2800W	2000W
Sensitivity 1W@1M	95 dB	97 dB	98 dB	98 dB	100 dB	99 dB
System Impedance	8 ohm	8 ohm	8 ohm	8 ohm	4 ohm	4 ohm
Woofers	8"	10"	12"	15"	Dual 15"	18"
Woofers Voice Coil	38mm / 1.5"	50.8mm / 2"	66mm/2.6"	66mm/2.6"	66mm/2.6"	100mm/4.0"
Tweeter	1" Titanium	1" Titanium	1.8" Titanium	1.8" Titanium	1.8" Titanium	-
Horn and System Dispersion	70° x 70° Conical	70° x 70° Conical	90° x 70°	90° x 70°	90° x 70°	-
Crossover Design	3rd order with HF bulb protection	3rd order with HF bulb protection	3rd order with HF bulb protection	3rd order with HF bulb protection	3rd order with HF bulb protection	Selectable LPF
Exterior (Standard / Deluxe Models)	Scratch-proof paint	Scratch-proof paint	Carpet / Scratch-proof paint	Carpet / Scratch-proof paint	Carpet / Scratch-proof paint	Carpet / Scratch-proof paint
Grille	Powder coated 18 gauge steel with acoustically transparent foam	Powder coated 18 gauge steel with acoustically transparent foam	Powder coated 18 gauge steel with acoustically transparent foam	Powder coated 18 gauge steel with acoustically transparent foam	Powder coated 18 gauge steel with acoustically transparent foam	Powder coated 18 gauge steel with acoustically transparent foam
Wood type (Deluxe Models)	Plywood / MDF	Plywood / MDF	15mm MDF (Plywood / MDF)	15mm MDF (Plywood / MDF)	18mm MDF (Plywood / MDF)	18mm MDF (Plywood / MDF)
Pole Mount	Metal Pole Mount	Metal Pole Mount	Metal Pole Mount	Metal Pole Mount	-	Metal Pole Mount
Handles (Deluxe Models)	Metal handle (Integrated)	Metal handle (Integrated)	Metal handles (Integrated)	Metal handles (Integrated)	Metal handles (Integrated)	Metal handles (Integrated)
Connectors	Speakon x 2	Speakon x 2	Speakon x 2	Speakon x 2	Speakon x 2	Speakon x 2
Net Weight	11.20kg/24.7lbs	14.20kg/31.30lbs	23.5kg/51.7lbs	28.5kg/62.7lbs	50kg/110lbs	47kg/103.4lbs
Unit Dimension (HxWxD)	450x285x275mm (17.7x11.2x10.8in)	505x330x325mm (19.9x13.0x12.8in)	627x395x370mm (24.7x15.5x14.6in)	717x460x435mm (28.2x18.1x17.1in)	1170x460x435mm (46.1x18.1x17.1in)	535x630x620mm (21.1x24.8x24.4in)