

VERSATAP 30

4" 2-Way Speaker with Transformer

VERSATAP 50

6-1/2" 2-Way Speaker with Transformer



Versatap 30 Features

- ▶ Power capacity: 30W (8 Ω)
- ▶ Sensitivity: 84 dB SPL @ 1W / 1M
- ▶ Frequency response: 120Hz to 20kHz / 75Hz to 20kHz
- ▶ 4" poly carbon woofer and 1" soft dome
- ▶ Built-in 70.7 V transformer with 4 tap positions (2, 4, 8, 16W) and 8 Ω bypass
- ▶ Compact and lightweight
- ▶ Moisture resistant
- ▶ Aluminum enclosure, available in both black and white
- ▶ U-mount bracket included

Versatap 50 Features

- ▶ Power capacity: 50W (8 Ω)
- ▶ Sensitivity: 90 dB SPL @ 1W / 1M
- ▶ Frequency response: 120Hz to 20kHz / 75Hz to 20kHz
- ▶ 6.5" poly carbon woofer and 1" soft dome
- ▶ Built-in 70.7 V transformer with four tap positions (2.5, 5, 10, 20W) and 8 Ω bypass
- ▶ Compact and lightweight
- ▶ Moisture resistant
- ▶ Aluminum enclosure, available in both black and white
- ▶ U-mount bracket included

Description

Versatap Series are contractor-friendly speakers. Each speaker is fitted with a 100V (70.7V available) line transformer, 4 power rating tap positions and an 8 ohms bypass position to allow for almost universal application in any PA system. The cabinet of the Versatap 30 is lightweight and of aluminum construction. It provides a strong, rigid housing, weather resistant capability, and is available in black or white.

VERSATAP SERIES

Contractor Speakers

Dimensions

VERSATAP 30 | VERSATAP 50



VERSATAP 30



VERSATAP 50

Specifications

	VERSATAP 30	VERSATAP 50
Maximum Power Rating	30 watts (8 ohms)	50 watts (8 ohms)
Frequency Response	120Hz~20KHz	75Hz~20KHz
Sensitivity@ 1W/1M, 1KHz	84dB	90dB
Woofer Size	4" Polycarbon	6.5" Polycarbon
Tweeter Size	1" Soft dome	1" Soft dome
70.7 Tap Positions	2, 4, 8, 16W	2.5, 5, 10, 20W
Dimensions (HxWxD)	184.2x114.3x108 mm (7.25"x4.5"x4.25")	292x197x210 mm (11.5"x7.75"x8.25")
Weight	1.58 kg (3.5 lbs)	3.5 kg (7.7 lbs)



VERSATAP U-MOUNT BRACKET