

# Sound Ambassador 75/120 Deluxe

**Sound Ambassador 75 Deluxe**  
**Sound Ambassador 120 Deluxe**

75 Watt Mobile Sound System  
120 Watt Mobile Sound System

Versatile function packed in an elegant form

Available CD/Cassette/MP3 modules for maximum flexibility

Two built-in wireless microphones for superior performance

Link out for connecting extra unit and optional passive speaker unit for more coverage

A portable, compact all-in-one design

Reclined monitor use available

## FEATURES

- ▶ Portable sound system with retractable trolley wheels
- ▶ Optional wireless microphones (UHF or VHF), CD player, MP3 player, and audio cassette recorder
- ▶ 100-120 / 200-240 VAC switching power supply
- ▶ 10" 2-way speaker system (120 watts @ 8 ohms)
- ▶ Built-in DC charging circuit
- ▶ 24 V DC supply from two built-in, maintenance-free lead acid type rechargeable batteries
- ▶ Slot for choice of two UHF/VHF PLL synthesized diversity or fixed frequency type wireless receiver modules
- ▶ Built-in diversity receiving UHF and VHF antennas
- ▶ One XLR and one 1/4" phone jack for wired microphone input
- ▶ 1/4" phone jacks and RCA jacks for line-level input and output
- ▶ Cassette recorder with pitch control
- ▶ CD player with anti-shock function
- ▶ Built-in limiter and protection circuitry to minimize distortion and overload
- ▶ Individual volume control for wired and wireless microphones
- ▶ Master volume control
- ▶ Switched and unswitched speaker output jacks
- ▶ Tripod stand adapter included



The Sound Ambassador Deluxe is a totally mobile, self-contained sound system. The unit comes packed with a 10" speaker, built-in amplifier and rechargeable batteries, and can be customized to include anti-shock CD player, MP3 player, audio cassette player/recorder and up to two wireless UHF microphones. A pull-out luggage handle and wheels make travel easy, but retract when in use to become invisible. Other important features include XLR and 1/4" microphone inputs, and a line input channel with 1/4" and mini stereo jacks, all with individual volume controls. A Line Out channel with 1/4" phone and 1/8" mini stereo jacks enables two Sound Ambassadors to be linked together, as well as the effortless addition of external digital recording devices. Additional speakers can be added to share the power from the amplifier, or the built-in speak can be turned off and power routed to external speakers. The unit is topped off with a 2-band system EQ, master volume control, built-in limiter, protection circuitry and tripod stand mount. All of these features combine to make the Sound Ambassador Deluxe a must-have for traveling presenters, small conferences, schools, classrooms, touring bands, clubs and karaoke.

# PHONIC

# Sound Ambassador 75/120 Deluxe

## Specifications

|   | Sound Ambassador 75 Deluxe   | Sound Ambassador 120 Deluxe  |
|---|--|--|
| <b>Woofers</b>                          | 10"  | 10"  |
| <b>Tweeter</b>                          | 1" compression driver  | 1" compression driver  |
| <b>Amplifier (watts), RMS</b>           | 75 Watt @ 4 ohm; 50 Watt @ 8 ohm   | 120 Watt @ 4 ohm; 75 Watt @ 8 ohms   |
| <b>Inputs &amp; Outputs</b>             | 1x XLR mic, 1x 1/4" mic, 1x1/4" & 1x mini stereo line in; 1x 1/4" & 1x mini-stereo line out, 2x 1/4" speaker out | 1x XLR mic, 1x 1/4" mic, 1x1/4" & 1x mini stereo line in; 1x 1/4" & 1x mini-stereo line out, 2x 1/4" speaker out |
| <b>Tone control</b>                     |  |  |
| Treble                                  | +/- 15dB @10k Hz   | +/- 15dB @10k Hz   |
| Bass                                    | +/- 15dB @ 80Hz  | +/- 15dB @ 80Hz  |
| <b>Frequency response (-10dB point)</b> | 50Hz~20KHz   | 50Hz~20KHz   |
| <b>Indicator</b>                        |  |  |
| Battery Full                            | Green  | Green  |
| Charging LED                            | Red (flashing)   | Red (flashing)   |
| Power LED                               | Blue   | Blue   |
| <b>Appearance</b>                       |  |  |
| Retractable Trolley                     | Yes  | Yes  |
| Wheels                                  | Yes  | Yes  |
| Handle                                  | on top   | on top   |
| Mount standable                         | 35mm tripod stand socket   | 35mm tripod stand socket   |
| Floor monitor version                   | Yes  | Yes  |
| <b>Built-In limiter</b>                 | Yes  | Yes  |
|   | thermal, subsonic, RF protection, Output DC offset, Power on/off muting and HF driver protection                 | thermal, subsonic, RF protection, Output DC offset, Power on/off muting and HF driver protection                 |
| <b>Built-In Battery</b>                 | 2x 4.5Ah   | 2x 4.5Ah   |
| <b>Power Requirement</b>                | 100-240VAC, 50/60Hz, or 2x battery power, or external 24-32VDC power   | 100-240VAC, 50/60Hz, or 2x battery power, or external 24-32VDC power   |
| Dimensions (HxWxD)                      | 24"x11.8"x13.8" (612x300x350 mm)   | 24"x11.8"x13.8" (612x300x350 mm)   |
| <b>Weight</b>                           | 43 lbs (19.5 kg)   | 45.2bs (20.5 kg)   |

### Optional Accessories:

- UM 30** Wireless Handheld System
- UM 40** Wireless System with Lavalier Mic
- UM 50** Wireless System with Headset Mic
- MK 3-SA** Wall/Ceiling Mounting Kit